

surestep® fast fit



Surestep Fast Fit safety flooring is a genuine safety vinyl suitable for an adhesive free installation. It can be laid over a variety of existing subfloors, including fresh, damp concrete substrates.

Surestep's PUR Pearl finish ensures it is both stain and chemical resistant, making it easy to clean and perfect for demanding commercial applications where a quick turnaround and minimal disruption is required, but slip resistance is a priority.

- Genuine **≥ 36 Safety flooring**
- **Adhesive free solution**
- **Quick turnaround, minimal disruption and low VOCs**
- **Impact sound reduction of 14 dB**

Description	Sheet safety vinyl	
Dimensions	Roll width 2m Roll length ≤27 Im	
Total thickness	EN ISO 24346	2.0mm
Thickness wear layer	EN ISO 24340	0.7mm
Collection size	6 / 6	
Application	EN ISO 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
UK	BS EN 14041:2004	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30



6171082 | snow LRV 75

For more information on this range scan the QR code.



6171032 | smoke LRV 47



618802 | elegant oak LRV 32



Surestep Fast Fit 618942 | natural oak



6171922 | concrete LRV 28



618942 | natural oak LRV 26



617122 | cool concrete LRV 37


Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Please note: Digital representations may vary from the actual product.
Please order a sample to see the full effect. Contact 0800 731 2369.



6171952 | elephant LRV 19



618572 | black seagrass LRV 13



617172 | black concrete LRV 8



617162 | grey concrete LRV 17



6171992 | charcoal LRV 6



6171262 | umber LRV 19



Surestep Fast Fit 617122 | cool concrete + 618942 | natural oak